




SENS-CUR600

Technical data sheet

Document version 1.0 | Released on: 27. March 2025

Schematic diagram



Dimensions of the SENS-CUR600 in mm

| 1 | Front view |
|---|-----------------------------------------------------|
| 2 | Side view |
| 3 | View from below |
| 4 | Schematic diagram for connecting the current sensor |

2

Technical data


| Electrical specifications | Values | | | |
|--------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|
| Primary rated current (amps) 50 Hz / 60 Hz | 600 A (30 - 720 A max.) | | | |
| Turns ratio | 1:6000 | | | |
| Transformation ratio | 600 A / 100 mA | | | |
| Resistance at 20°C (Ω) | 360 max. | | | |
| Accuracy at Rb ≤10 Ω | 0.5% | | | |
| Dielectric withstanding voltage | 4 KV / 1 mA / 1 min | | | |
| Protection category | 600 V CAT III | | | |
| Insulation resistance | DC500 V / 100 MΩ min | | | |
| Housing | Insulated plastic housing, recognised according to UL 94- V0 | | | |
| Temperature range during operation | Operation: -40°C to 85°C | | | |
| Temperature range during storage | Storage: -40°C to 90°C | | | |
| Ambient conditions | Controlled environment, pollution degree 2, operating altitude up to max. 2,000 m | | | |

| Mechanical specifications | Values | | | |
|--------------------------------|----------------------------------------------------|--|--|--|
| Housing | PA66 | | | |
| Opening angle | 180° | | | |
| Connecting cable | UL1015 22AWG PVC cable (white, black) 105°C, 600 V | | | |
| Length of the connecting cable | 3 m | | | |
| Opening for the power cable | 34×40 mm | | | |
| Weight | 330 g | | | |

Measurement results (TA = 25°C at 50 Hz)

| Current(A) | | 30 | 120 | 600 | 720 | $DCR(\Omega)$ |
|------------|--------------|--------|--------|--------|--------|---------------|
| SPEC. | <i>f</i> (%) | ±1.5 | ±0.75 | ±0.5 | ±0.5 | 360max. |
| | δ(') | ±90 | ±45 | ±30 | ±30 | Journay. |
| 1# | <i>f</i> (%) | -0.610 | -0.364 | -0.060 | -0.053 | 316.3 |
| 1# | δ(') | 11.2 | 7.7 | 5.3 | 5.1 | 310.3 |
| 2# | <i>f</i> (%) | -0.401 | -0.226 | -0.039 | -0.027 | 312.9 |
| Ζπ | δ(') | 12.4 | 10.7 | 6.0 | 5.3 | |
| AVE | <i>f</i> (%) | -0.506 | -0.295 | -0.050 | -0.040 | 314.6 |
| AVL | δ(') | 11.8 | 9.2 | 5.7 | 5.2 | 314.0 |
| MAX | <i>f</i> (%) | -0.401 | -0.226 | -0.039 | -0.027 | 316.3 |
| IVIAA | δ(') | 12.4 | 10.7 | 6.0 | 5.3 | 310.3 |
| MIN | <i>f</i> (%) | -0.610 | -0.364 | -0.060 | -0.053 | 312.9 |
| IVIIIN | δ(') | 11.2 | 7.7 | 5.3 | 5.1 | 512.8 |

Power curve



This document is available in electronic form in the download portal of in.hub. Printed versions or copies not explicitly provided by in hub are deemed uncontrolled

The original language of this document is German.

Made in Germany

Service & Support: service@inhub.de | https://community.inhub.de/

in.hub Download portal: https://download.inhub.de/



in.hub GmbH Technologie-Campus 1 DE-09126 Chemnitz

+49 371 335 655 00 info@inhub.de